



QLSP01WXL-190
(3014 High Efficiency LED)



Product Outline:

These high output reflector type Tube LEDs are available in warm white /neutral white / pure white / and cold white to suit customer's application. These LEDs are equipped with heat sink to enhance operating performance. With special binning technology, these LEDs are ideal for architecture lighting and special lighting needs.

Features:

- High brightness output @ 65mA
- Package Dimension = 3.0mmX1.4mmX0.65mm
- CRI = 80 and above
- Available in warm white / neutral white / pure white / and cold white
- ASNI Binning
- RoHS compliant
- Custom Bin available upon special request


Application:

- Architecture Lighting
- Security / garden lighting
- Interior Lighting
- General lighting

Compliance and Certification:




Mechanical Property: (Dimension)



* All dimensions are in millimeters, * Tolerances are $\pm 0.10\text{mm}$.

Recommended Solder footprint:



- * All dimensions are in millimeters.
- * The LEDs is designed to be reflow soldered on to a PCB. IF dip soldered that QL cannot guarantee its reliability.
- * Reflow soldering must not be performed more than twice.



Characteristics

■ Absolute Maximum Ratings

(Ta=25°C)

Parameter	Symbol	Rating	Unit
DC Forward Current	If	150	mA
Power Dissipation	Pd	0.5	W
Pulse Forward Current	I _{fp}	200	mA
LED Junction Temperature	T _J	120	°C
Storage Temperature	T _{stg}	-40 ~ 100	°C
Operation Temperature	T _{opr}	-40 ~ 85	°C
Soldering Temperature	T _{sol}	260 < 5 sec	°C

- (1) Proper current rating must be observed to maintain junction temperature below maximum at all time
 (2) I_{FP} Condition: t < 100 μs ; D = 0.001 ; Ta= 25 °C

■ Electrical / Optical Characteristic


(Ta=25 oC)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V _f	65mA	2.8		3.4	V
Color Rendering Index	R _a		80			
View Angle	θ			120		deg
Thermal Resistance	R _{th}			45		oC/W

- (1) Tolerance of measurement: VF=+/- 0.1V
 (2) The CRI tolerance is ±2.
 (3) Thermal resistance is calculated from junction to solder



■ Specification Chromaticity Coordinates




ANSI CCT	Color Space	Target Center point (cx,cy)	Major Axis,a	Minor Axis,b	Ellipse Rotation Angle
2700K	3-step MacAdam ellipse	(0.4578,0.4101)	0.0081	0.0042	53.70°
2700K	5-step MacAdam ellipse	(0.4578,0.4101)	0.0135	0.007	53.70°
3000K	3-step MacAdam ellipse	(0.4338,0.403)	0.0083	0.00408	53.22°
3000K	5-step MacAdam ellipse	(0.4338, 0.403)	0.0139	0.0068	53.22°
4000K	3-step MacAdam ellipse	(0.3818,0.3797)	0.0094	0.00402	53.72°
4000K	5-step MacAdam ellipse	(0.3818,0.3797)	0.0157	0.0067	53.72°



5000K	3-step MacAdam ellipse	(0.3447,0.3553)	0.0082	0.00354	59.62°
5000K	5-step MacAdam ellipse	(0.3447,0.3553)	0.0137	0.0059	59.62°
5700K	3-step MacAdam ellipse	(0.3287,0.3417)	0.0075	0.0032	59.09°
5700K	5-step MacAdam ellipse	(0.3287,0.3417)	0.0124	0.00533	59.09°
6500K	3-step MacAdam ellipse	(0.3123,0.3282)	0.0067	0.00285	58.57°
6500K	5-step MacAdam ellipse	(0.3123,0.3282)	0.0112	0.00475	58.57°

CIE binning code



Forward Voltage (V_F) Bin:

VF Rank @ 65mA			
Code name	Min.	Max.	Units
0	2.8	2.9	V
1	2.9	3.0	
2	3.0	3.1	
3	3.1	3.2	
4	3.2	3.3	
5	3.3	3.4	

The forward voltage tolerance is $\pm 0.1V$

Luminous Intensity Bin:


Intensity Rank (mcd) @ 65mA			
Code name	Min.	Max.	Units
QK	22.5	25	lm
QL	25	28	
QM	28	31.5	
QN	31.5	36	

Luminous intensity tolerance is $\pm 7\%$




■ Characteristic Curves


(1) Color Spectrum




(2). Typical Representative Spatial Radiation Pattern



(3). Forward Current vs Relative Luminous Intensity



(4). Forward Current vs Forward Voltage



■ Reliability test:

No	Item	Condition	Time/Cycle	Sample size
1	Steady State Operating Life of Room Temperature	25°C Operating	1000 Hrs	20 pcs
2	Steady State Operating Life of Low Temperature -40°C	-40°C Operating	1000 Hrs	20 pcs
3	Steady State Operating Life of Low Temperature 60°C	60°C Operating	1000 Hrs	20 pcs
4	Steady State Operating Life of Low Temperature 85°C	85°C Operating	1000 Hrs	20 pcs
5	Low temperature storage -40°C	-40°C Storage	1000 Hrs	20 pcs
6	High temperature storage 100°C	100°C Storage	1000 Hrs	20 pcs
7	Steady State Operating Life of High Humidity Heat 60°C/90%	60°C/90% Operating	1000 Hrs	20 pcs
8	Steady State Pulse Operating Life Condition	25°C 10Hz duty=1/10 Operating	200 Cycle	20 pcs
9	Resistance to soldering heat on PCB (JEDEC MSL3)	pre-store@60°C, 60%RH for 52hrs Tslid max.=260 10sec	3 Times	20 pcs
10	Heat Cycle Test (JEDEC MRC)	25°C~65°C~-10°C, 90%RH, 24hr/1cycle	10 Cycle	20 pcs
11	Thermal shock	-40°C/ 20minr~ 5minr~100°C /20min	300 Cycle	20 pcs


■ Judgment Criteria:

Item	Symbol	Test Condition	Judgment Criteria
Forward Voltage	Vf	65 mA	$\Delta Vf < 10\%$
Luminous Flux	Iv	65 mA	$\Delta Iv < 30\%$



■ Solder Profile:

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Temperature Min(T_{smin})	100°C	150°C
Temperature Max(T_{smax})	150°C	200°C
Time(t_a) from (T_{smin} to T_{smax})	60-120 seconds	60-120 seconds
Ramp-up rate(T_L to T_p)	3°C/second max.	3°C/second max.
Liquidous Temperature(T_L)	183°C	217°C
Time(t_L) maintained above T_L	60-150 seconds	60-150 seconds
Peak package body temperature(T_p)	235°C	260°C
Time within 5°C of Actual Peak temperature (t_p)	20seconds*	30 seconds*
Ramp-down rate(T_p to T_L)	6°C/second max.	6°C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.




■ Taping & Packing:




Item	Spec	Tol.(+/-)	Item	Spec	Tol.(+/-)
W	8.00	±0.1	P2	2.00	±0.05
E	1.75	±0.1	P0 x 10	40.00	±0.2
F	3.50	±0.05	t1	0.23	±0.05
D	1.50	+0.1,-0	A0	1.55	±0.1
D1	1.00	±0.1	B0	3.20	±0.1
P0、P1	4.00	±0.1	K0	0.95	±0.1

Unit : mm





■ Labeling



Quantity: XXXX



Quelighting P/N: XXXXXX



Lot number: XXXXX



Iv Bin: XX
Color Bin: XX
Vf Bin: XX
Date Code: XXXX

■ Ordering Information:

Part #	Multiple Quantities	Quantity per Reel
QLSP01WXL-190		2000 /4000 pcs

■ Revision History:

Revision Date:	Changes:	Version #:
02-27-2018	Initial release	1.0
09-23-2019	Updated the performance	1.1

